

Bianco Oil Aqua

raw wood effect

0,375 l - 1 l - 2,5 l - 10 l



Description:

Bianco Oil Aqua is a water-soluble wood coating that lightens the surface, protects against UV darkening and does not enhance wood grain structure. The silky matt finish is durable, dirt- and water-repellant. The wood retains its natural appearance.

Bianco Oil Aqua is perfect for floors, stairs, furniture and paneling. It can be used inside furniture drawers and cabinets. It conforms to the International Toy Standard EN 71/3 and the Sweat and Saliva Resistance standard DIN 53 160.

Bianco Oil Aqua contains a minimum of 76% renewable and mineral raw materials.

Ingredients:

Water, aliphatic Polyurethane made from castor oil, rice wax, silicic acid, alcohol, Polysiloxane, titanium dioxide, Preservative: Benzisothiazolinon and a blend of 5-Chlor-2-methyl-2H-isothiazol-3-on and 2-Methyl-2H-isothiazol-3-on.

Directions for Use:

1. Preparation The surface must be clean, dry, and free of old coatings. Remove grease stains with white spirit. Sand floors with 180 - 220 grit and furniture with 240 grit paper

2. Application Mix well before use. Apply thinly and evenly with a brush, short pile roller or sprayer. The surface is dry to touch in 2 hours and can be sanded for recoating in 6 hours.

Sand with 220-240 mesh between coats. Apply the second coat as with the first. Two coats provide a durable, water-repellant surface. For a smoother surface, sand and apply a third coat as described above.

Important: test product on a small surface for compatibility. Work quickly wet-on-wet and avoid painting a section that has dried.

Do not apply in air or surface temperatures below 16°C.

To ensure homogeneous surfaces, mix product from different containers.

Ensure adequate ventilation during all phases of work.

The natural oils can develop a characteristic odor while drying.

Tool Cleaning Wash immediately after use with water and soap. Soak dried on tools in BIOFA® Brush Cleaner 0600 overnight.

Surface Cleaning and Maintenance Avoid all dirt during the first week. Do not use wet mops. Afterwards, sweep dirt and wash with a cloth dampened with BIOFA® Nacasa® Household Cleaner 4010 in warm water or BIOFA® All-Purpose Ready To Use Spray Cleaner 4020. Can be polished with Naplana Liquid Polish 2080 (original) or 2085 (Skid Stop)

Drying Times:

Dries to touch in 2 hours. Can be sanded in 6 hours. Fully cured in 2 days. Drying times vary with temperature, room humidity and surface type.

Coverage:

1. Coat: 70-80 ml/m² = 12-14 m²/l

2. Coat: 50-70 ml/m² = 14-20 m²/l

Coverage depends on the absorbability of the surface.

Storage:

Keep cool, well sealed and in a dry location. Unopened, use within 24 months.

Disposal:

Discard unused liquid and wet containers according to local regulations. Small amounts of liquid oil and saturated tools can be dried and discarded with household waste.

Recycle only emptied and cleaned cans.

Do not release into the environment or sewers!

EAK Waste code 08 01 12

Hazard warnings and Safety Instructions:

Contains 1,2-Benzisothiazol-3(2H)-on, 5-Chlor-2-methyl-2H-isothiazol-3-on and 2-Methyl-2H-isothiazol-3-on; can cause an allergic reaction. Allergen information: Tel.: +49(0)7164-9405-0. Keep out of reach from children. If medical attention is required, keep the label or this sheet handy. Avoid contact with eyes, skin or clothing. Wash eyes or skin with plenty of water. Ensure sufficient skin and eye protection. Do not inhale spray or vapors. Use a suitable A2/P2 mask when spraying or P2 when sanding.

A safety data sheet is available on request!

GISCODE: BSW20

EU-VOC limit for category: 140 g/l (2010)

8689 contains max. 50 g/l VOC.

As of: 2022/10/12